

CARBON STEEL HOSE REELS - SPRING REWIND AND MANUAL REWIND

Carbon Steel Hose Reel Model: RL-N800-CS

- Carbon Steel Spring rewind reel with narrow frame and compact mounting base
- Non sparking ratchet assembly
- Declutching arbor to prevent damage from reverse winding
- Standard inlet 90° balanced pressure swivel joint 1" female NPT threads
- Standard outlet 1" female NPT threads
- Pressures to 1000 psi (69 bar)
- Temperatures from -40°F to +250°F (-40°C to +121°C)
- Consult factory for other pressures and temperatures
- 4-way roller assembly
- Constant tension is available - consult factory



Carbon Steel Hose Reel Model: RL-800-CS

- Rollformed channel frame for heavy-duty applications
- Non sparking ratchet assembly
- Declutching arbor to prevent damage from reverse winding
- Standard inlet 90° balanced pressure swivel joint 1" female NPT threads
- Standard outlet 1" female NPT threads
- Pressures to 1000 psi (69 bar).
- Temperatures from -40°F to +250°F (-40°C to +121°C)
- Consult factory for other pressures and temperatures
- 4-way roller assembly
- Constant tension is available - consult factory



Carbon Steel Hose Reel Model: MRL 1800-CS

- Manual Rewind Reel for long lengths of hose
- Choose disc rewind or removable direct crank rewind
- Supplied with spring-actuated pin lock
- Standard inlet 90° balanced pressure swivel joint 1" female NPT threads
- Standard outlet 1" female NPT threads
- Pressures to 1000 psi (69 bar)
- Temperatures from -60°F to +250°F (-51°C to +121°C)
- Consult factory for other pressures and temperatures
- Optional bronze or aluminum swivel joint and stainless steel hub assembly and riser are available

