

STAINLESS STEEL HOSE REELS - SPRING REWIND AND MANUAL REWIND

Stainless Steel Hose Reel Model: RL-N800-SS

- Spring rewind reel with narrow frame and compact mounting base
- Non sparking ratchet assembly
- Declutching arbor to prevent damage from reverse winding
- Standard inlet 90° ball bearing swivel joint 1" female NPT threads
- Standard outlet 1" female NPT threads
- Pressures to 1000 psi (69 bar)
- Temperatures from +20°F to +400°F (-7°C to +204°C)
- Consult factory for other pressures and temperatures
- 4-way roller assembly
- Constant tension is available - consult factory



Stainless Steel Hose Reel Model: RL-800-SS

- Square tubing frame for heavy-duty applications
- Non sparking ratchet assembly
- Declutching arbor to prevent damage from reverse winding
- Standard inlet 90° ball bearing swivel joint 1" female NPT threads
- Standard outlet 1" female NPT threads
- Pressures to 1000 psi (69 bar)
- Temperatures from +20°F to +400°F (-7°C to +204°C)
- Consult factory for other pressures and temperatures.
- 4-way roller assembly
- Constant tension is available - consult factory



Stainless Steel Hose Reel Model: MRL 1800-SS

- Economical manual rewind reel for long lengths of hose
- Choose disc rewind or removable direct crank rewind
- Supplied with spring-actuated pin lock.
- Standard inlet 90° ball bearing swivel joint 1" female NPT threads
- Standard outlet 1" female NPT threads
- Pressures to 1000 psi (69 bar)
- Temperatures from +20°F to +400°F (-7°C to +204°C)
- Consult factory for other pressures and temperatures
- 4-way roller assembly
- Constant tension is available - consult factory

