



**LED  
ETL HAZLOC  
FIXTURE**



**EX20-1000**



**FEATURES**

- Hazardous location luminaire
- Washdown safe IP66 rating
- Perfect for environmental chambers, beverage process, sightglasses, sight flow indicators and manways
- AC or DC operations
- High power CREE™ COB LED
- Proven LED driver for ultimate reliability
- Stainless steel machined housing provides separate compartments for electronics and wiring
- Designed for harsh environment operating capability
- High grade optics for exceptional performance
- Mounting brackets and tri-clamp mounting adapter available (sold separately)

**PRODUCT SPECIFICATIONS**

**Electrical Specifications:**

- Power Input: AC 120-277V, 50/60 Hz
- Power Input: DC 8-36 VDC
- Power Factor: ≥0.9
- THD: <20% @ full load

**COB LED TECHNOLOGY**

- Cree XLamp® COB LED technology
- Correlated color temperature (CCT nominal): 6500K
- COB light emitting size (LES): 9.8
- Heatsink interface for rapid COB heat dissipation
- Typical COB lifetime: 36,000 hrs

Rating: ETL Listed: UL 844 & CSA C22.2 #137

This fixture is suitable for use in the following locations as defined by the National Electrical Code:

**Class Division Groups:** Class 1, Div 1, Groups C&D / Class 1, Div 2, Groups C&D

**Temperature:** T4 & T5

MODEL NO.	SUPPLY VOLTAGE	LED CURRENT	NOMINAL INPUT POWER	LUMENS	TEMPERATURE CODE
EX20-1000-01	120/(220-240)/277 VAC	350 mA	15W	1900	T4
EX20-1000-02	8-36 VDC	350 mA	15W	1900	T5
EX20-1000-03	120/(220-240)/277 VAC	500 mA	21W	2600	T4
EX20-1000-04	8-36 VDC	500 mA	19W	2600	T5

**800.554.1394**

357 Spook Rock Rd | Suffern, NY | 10901  
 sales@ARCHONind.com  
 Fax 845.368.3040